

**SPECIFIC REQUIREMENTS FOR TRANSPORT  
AT THE ENTRY POINT ZEEBRUGGE LNG TERMINAL**

	<b>Unit</b>	<b>Min.</b>	<b>Max</b>
<b>Gross Calorific Value</b>	kWh/m <sup>3</sup> (n)	10.80	12.77
<b>Wobbe Index</b>	kWh/m <sup>3</sup> (n)	13.67	15.56
<b>Pressure for offtake by Fluxys<sup>(1)</sup></b>	Barg	55	80
<b>Temperature</b>	°C	2	38
<b>Hydrocarbon Dewpoint</b>	°C from 0 Barg up to 69 Barg	-	Minus 2
<b>Water Dewpoint</b>	°C at 69 Barg	-	Minus 8
<b>Oxygen content (O<sub>2</sub>)</b>	ppm by vol	-	1000
<b>Carbon dioxide content (CO<sub>2</sub>)</b>	Mole %	-	2.0
<b>Hydrogen sulphide content (H<sub>2</sub>S) (inclusive of COS) (as S)</b>	mg/m <sup>3</sup> (n)	-	5
<b>Total sulphur at any time (as S)</b>	mg/m <sup>3</sup> (n)	-	30

(1) The shipper shall make available the Natural Gas at any pressure within that range as requested from time to time by Fluxys.

The Natural Gas delivered may not contain other elements and impurities (such as but not limited to methanol, condensates, gas odorants) to the extent that the Natural Gas delivered cannot be transported, stored and marketed in Belgium without incurring additional cost for quality adjustment.

The Natural Gas delivered may not contain any added odorants.